

Rubber Fab Technologies Group's X-TREME FLEX

RFXF- Smoothbore PFA with Convolute Hose Flexibility



Half the Minimum Bend Radius of
Conventional Smoothbore Fluoropolymer

Features:

- Smoothbore PFA Fluoropolymer lined hose
- Superior Flexibility
- Superior Kink Resistance
- Half the minimum bend radius of conventional smoothbore products
- Full Vacuum Rated
- Autoclavable
- Steam Cleanable at stated temperature/pressure ratings
- Stainless Steel Reinforced

Applications:

- Food & Beverage Processing
- Chemical Transfer
- Pharmaceutical processing
- Hot CIP Solutions

Approvals:

- 3A Sanitary Standard
- FDA 21 CFR 177.1550
- U.S.P. Class VI

FLEXIBILITY at the X-TREME

TUBE:

Smoothbore PFA Tube

REINFORCEMENT:

Bonded Wire Braid
Silicone
Textile Braided Composite

COVERS:

Stainless Steel Braid (Standard)
*Kynar® Braided, Red (Optional)
*Consult factory for temperature rating

TEMPERATURE:

-65°F to 325°F

Part #	I.D.	O.D.	Working Pressure @ 68F	Bend Radius inches	Vacuum Rating @ 72F
06RFXF	.375	.625	300	2.00	29.9
08RFXF	.500	.755	300	2.50	29.9
12RFXF	.750	1.04	250	3.00	29.9
16RFXF	1.00	1.29	250	4.00	29.9
24RFXF	1.50	1.85	200	7.00	29.9

RUBBER FAB

26 Brookfield Drive
Sparta, NJ 07871
Phone: 973-579-2959
Toll Free: 866-442-2959
Fax: 973-579-7275
Email: sales@rubberfab.com

RUBBER FAB
technologies group

www.rubberfab.com

Kynar® is a registered trademark of Arkema, Inc. Corporation